

PK Machinery

Technical Parameters of ZS Linear Vibrating Screen

Model	Capacity		Vibration Motor		Frequency (min ⁻¹)
	Granularity (mm)	Capacity (t/h)	Model	Power (kW)	
ZS0.4×1.2	≤30	6	YZ0-5-4	0.4×2	1500
ZS0.5×1.2	≤30	7	YZ0-8-4	0.75×2	1500
ZS0.6×1.2	≤30	8	YZ0-8-4	0.75×2	1500
ZS0.7×1.2	≤30	12	YZ0-16-4	1.5×2	1500
ZS0.8×1.6	≤30	14	YZ0-16-4	1.5×2	1500
ZS0.9×1.8	≤30	15	YZ0-20-4	2.0×2	960
ZS0.9×2.4	≤30	16	YZ0-20-4	2.0×2	960
ZS1.2×2.4	≤30	20	YZ0-30-4	2.5×2	960
ZS1.2×3.0	≤30	24	YZ0-30-4	2.5×2	960
ZS1.5×3.0	≤30	28	YZ0-30-4	3.7×2	960

Model	Exciting Force (kN)	Double- amplitude (mm)	Weight (kg)		
			Single-deck	Double-deck	Three-deck
ZS0.4×1.2	5.0×2	2~4	160	189	218
ZS0.5×1.2	8.0×2	2~4	260	297	335
ZS0.6×1.2	8.0×2	2~4	280	317	355
ZS0.7×1.2	16.0×2	2~4	420	468	515
ZS0.8×1.6	16.0×2	2~4	457	520	554
ZS0.9×1.8	20.0×2	2~4	870	927	984
ZS0.9×2.4	20.0×2	2~4	1200	1289	1305
ZS1.2×2.4	30.0×2	3~5	1500	1625	1750
ZS1.2×3.0	30.0×2	3~5	1760	1913	2066
ZS1.5×3.0	30.0×2	3~5	2400	2629	2858



Tel: +86 373 589 0799 E-mail: support@pkmachinery.com
Address: 289 Yellow River Road, Xinxiang City, China